

## FEATURES & BENEFITS

The supporting cradle allows easy movement with fork lift tines or can be slung overhead from the dedicated lifting points. Designed to store and transport a variety of liquids up to a maximum of 1350kg/m<sup>3</sup>.

- Manufactured from EB Equipment's unique blend of polyester glass reinforced plastic
- Corrosion resistant and UV stabilised for long life
- Top access hatch incorporating ventilation fitted as standard
- Single piece construction eliminates seams, joints and bolted sections
- Steel work is fully welded and hot dip galvanised
- Internal baffles (8Cu.m and above)
- Oval inspection hatch as standard
- 3" PN16 flange inlet / outlet
- 110mm roof mounted vent complete with internal matrix
- Custom sizes available
- Optional extras available including:
  - » Flanges
  - » Valve sets
  - » Pipework

Optional colours available in **ANY** RAL/BS colour, see examples:

Colours are for references purposes only and may not be accurately reproduced in printing.



TANK Part No:	VOLUME	HEIGHT	WIDTH	LENGTH	CAPACITY	
					Tonnes 1000kg / m <sup>3</sup>	Tonnes 1350kg / m <sup>3</sup>
162205	5m <sup>3</sup>	1.8m	2.2m	2.6m	5T	6.75T
162208	8m <sup>3</sup>			3.3m	8T	10.8T
162210	10m <sup>3</sup>			4.0m	10T	13.5T
162212	12m <sup>3</sup>			4.8m	12T	16.2T
162215	15m <sup>3</sup>			5.7m	15T	20.25T

Bespoke sizes available on request, please speak to a member of our team.

V001 - 02/01/2019